

PAXLight™

Specifications

PAXLight™ Light Head

1. Operating Temperature: 0~48C (32~120F)
2. Storage Temperature: -20 to +85C.
3. Relative Humidity: 5% to 95% non-condensing.
4. Altitude: Max 10,000 feet
5. LEDs : 21 (12 white, 9 amber)



PAXLight™ Power Supply

1. Input Voltage 100~240 VAC, 50~60 Hz
2. Input Current 2A.
3. Output voltage 24VDC, max 5.0 A
4. Operating Temperature: 0~48C (32~120F)
5. Storage Temperature: -20 to +85C.
6. Relative Humidity: 5% to 95% non-condensing.
7. Altitude: Max 10,000 feet.
8. Cooling convection - non vented.
9. Power Cable (Black) 300V, 18/3 SJOOW water resistant flexible to -40C.
10. Control Cable (Grey) 600 V 18/3 water and crush resistant flexible to -40C.

Mechanical

1. Support Pole: 32"
2. Arm: 32" full reach
3. Body: 12" W x 13" L x 5" H, Weight 2.29 lbs.
4. Power Supply 1.9 lbs. (0.87kg) - 9"L x 3"W x 2" H



**NOTE: PAXLights can be
purchased individually.**

Light Output Comparison

